



If Nanolux doesn't make it, you don't need it.

LEDzx

Series Lights 630W

- 110V-277V wide voltage design, available with different NEMA power plugs for a wider range of voltage used.
- Folding design facilitates transportation and saves on shipping and storage costs.
- Modular patented design.
- Digital control buttons are used for smart digital dimming with dimming ranges of 105W, 210W, 315W, 420W, 525W, and 630W
- Smart digital bar protection system: Upon one or more bar failures the system will digitally protect working bars and the power supply allowing for continuous ongoing operation.
- IP65 design protects against environmental conditions such as moisture and dust.
- Included features: Random start, soft start, soft dimming, over-temperature, over-voltage and open/short circuit protection.
- Compatible with various 0-10V control systems.



- ✓ Use Sanan high-quality chips
- ✓ Foldable for easy handling
- ✓ Wide input voltage 110V-277V
- ✓ Light weight & compact design
- ✓ 0-10V wired lighting control





Specifications

Product	LEDzx Series Lights 630W
Product Code	80.01.0297
Light Output PPF	1650 $\mu\text{mol/s}$
Efficiency	2.62 $\mu\text{mol/J}$
Dimming	0-10V
Input Power	630W
Input Voltage	AC 110V-277V
Input Frequency	50/60Hz
Light Distribution	120°
Mounting Height	8" - 20" (20-50cm) above canopy
Operating Temperature	0°C ~ 35°C
Operating Humidity	0-95%
Thermal Management	Passive
Power Factor	> 0.97
Total Harmonic Distortion	< 10%
Requirement of Installment	Comply with ETL/FCC/CE/EAC certificate
Lifetime L90	> 50,000hrs
IP rating	IP65
Product Dimensions	1200x1150x70mm
Product Weight	10.6KG
Packaging Method	1PC/Carton (LED fixture with Driver)
Packaing Dimensions	1215x590x95mm
Gross Weight	12.2KG
Warranty	5 year standard warranty



Nominal Electrical Ac Input*

AC VOLTAGE	120V	208V	220V	240V	277V
AC Current	5.43A	3.05A	2,86A	2.62A	2.28A
AC Power	652W	635W	631W	631W	631W
Power Factor	0.99	0.99	0.99	0.98	0.98

* At 25°C (77°F) Ambient Temperature

